



用途 Use

LCB系列沥青泵主要用于抽吸、泵送和涂布高温沥青，它最适用于公路、桥梁、道路和广场等建筑工程中的沥青涂布作业。也可用于抽吸、泵送粘度较高的其它液体介质，如各种机械油、液压油、重油、渣油、各种植物油等。

LCB series pump is mainly to carry pitch under high temperature, and it is suitable to work at the place as high way bridge, road, and square. Also the pump can carry high viscosity liquid, as mechanical oil, hydraulic oil, heavy oil, dregs oil and all kinds of vegetable oil etc.

主要技术参数 Main technique parameter

型号 Type	LCB-50	LCB-100	LCB-150	LCB-200
额定流量 L/min	50	100	150	200
额定压力 MPa	1.0	1.0	0.8	0.8
真空度 MPa	-0.04	-0.04	-0.04	-0.04
额定转速 r/min	800	500	500	500
功率 kw	2.2	3.5	4.5	5.5
进出口径 diameter	G1"	G1 1/2"	G1 1/2"	G2"
净重 kg	17	30	35	40

安装尺寸 Mounting dimension

型号	b	d	D1	L1	L2	L3	L4	L5	L6	L9	H1	H2
LCB-50	6	20	G1"	36	40	27	80	42	300	185	81.5	108
LCB-100	8	28	G1 1/2"	46	50	32	70	62	340	222	109	145
LCB-150	8	28	G1 1/2"	46	50	32	70	76.5	370	222	109	145
LCB-200	8	28	G2	46	50	32	70	81	400	242	109	145