

## 特点

## Features

H型泵是抽除一般性气体或含有少量可凝性气体（此时应使用气镇阀）及不含灰尘气体的真空设备，本泵可单独使用，也可作为其它泵的前级泵，该型泵广泛应用于各行各业。

H type pump is another vacuum equipment which can suck off the normal gas or the gas mixed with little vapour (use the air brake valve when it's running), also the non-dust gas. It can be used both separately and as the previous pump of other pump. It's widely used in various area.



H-150

型号 Model	极限压力 Ultimate Pressure		抽气速率 Pumping Speed (L/s)	进气口径 Inlet Diam. (mm)	排气口径 Outlet Diam. (mm)	配用功率 Motor Power (kw)	供水量 Cooling Water Consumption (kg/h)	重量 Weight (kg)
	hpa	Torr						
1401	$1.3 \times 10^{-2}$	$1 \times 10^{-2}$	54	75	50	5.5	480	450
H-150	$1 \times 10^{-2}$	$8 \times 10^{-3}$	150	100	80	15	700	720
H-150D	$1 \times 10^{-2}$	$8 \times 10^{-3}$	150	105	80	11	450	896

SK-12P	9	665	5	80	970	18.5	70
2SK-25P	20	665	5	80	970	45	150