



用途及特点

Application & Features

SK/2SK水环式真空泵, 能耗少, 噪音低, 除能抽除一般性气体外, 也能抽吸易燃易爆气体和水蒸汽, 如果改变主要零件材质或防腐处理, 还能吸腐蚀性气体, 2YK油环真空泵, 真空度高, 适应性强, 广泛应用于冶金、化工、食品、电力、医药等部门的真空工艺处理中。

SK/2SK type of water circulating vacuum pump has such advantages: less power consuming, lower noise, can suck out normal gas, inflammable and explosive gas, and the water steam. If the main parts are changed with material or done anticorrosive treatment, it can also suck out the corrosive gas. 2YK type of oil circulating vacuum pump has high vacuum and can fit for operating strongly. It's widely used in the vacuum-plant treatment of metallurgy, medical industry, food, electrical power, medicine, etc.



SK-12



2SK-25



2YK-3



SK-1.5

型号 Model	极限压力 Ultimate Pressure		抽气速率 Pumping Speed (m ³ /min)	进气口径 Inlet Diam. (mm)	排气口径 Outlet Diam. (mm)	电机功率 Motor Power (kw)
	hpa	Torr				
SZ-1	160	120	1.5	70	70	4
SZ-2	130	100	3.4	70	70	7.5
SZ-3	80	60	11.5	125	125	22
SZB-8	150	110	0.84	G1"	G1"	3
SK-1.5	40	30	1.5	40	40	4
SK-3	80	60	3	50	50	5.5
SK-6	80	60	6	50	50	11
SK-12	40	30	12	80	80	18.5
SK-25	80	60	25	100	100	37
2SK-3	40	30	3	50	50	7.5
2SK-6A	35	25	6	50	50	11
2SK-12	35	25	12	80	80	22
2SK-25	35	25	25	100	100	45
SK-3T	40	30	3	50	50	5.5
SK-6T	40	30	6	80	80	11
SK-25T	40	30	25	100	100	45
SK-45T	46	35	45	150	150	75
2YK-3	6.6	5	3	50	50	7.5
2YK-6A	6.6	5	6	50	50	11
2YK-12	6.6	5	12	80	80	22
2YK-25	6.6	5	25	100	100	45